

SARSILMAZ



SAR9 SC GEN3

YARI OTOMATİK TABANCA / SEMI AUTOMATIC PISTOL

TEKNİK VERİ (TECHNICAL DATA)

KALİBRE (CALIBER)	9 x 19 mm
ÇALIŞMA SİSTEMİ (OPERATING PRINCIPLE)	YARI OTOMATİK (SEMI AUTO)
EMNİYET SİSTEMİ (SAFETY SYSTEM)	TETİK, İÇNE ve DÜŞME EMNİYETİ (TRIGGER, FIRING PIN and DROP SAFETY)
KAPASİTE (CAPACITY)	12 / 15 / 17 / 19 / 21 BULLETS
NAMLU UZUNLUĞU (BARREL LENGTH)	85 mm / 3.3"
TETİK AĞIRLIĞI (TRIGGER PULL)	20 - 30 N
NAMLU ÇIKIŞ HIZI (MUZZLE VELOCITY)	350 m/s
ETKİLİ MENZİL (EFFECTIVE RANGE)	50 m
YİV-SET (RIFLING)	6 SAĞ (6 RIGHT) - 1/10" (250 mm)

REV:0 - 24/01/2024



*Ebatlar 12 Kapasiteli şarjöre göre verilmiştir. The dimensions are provided according to a 12-round capacity magazine.

EBATLAR (DIMENSIONS)

1- TAM UZUNLUK (OVERALL LENGTH)	163 mm / 6.4"
2- YÜKSEKLİK (HEIGHT)	133 mm / 5.2"
3- GENİŞLİK (OVERALL WIDTH)	32 mm / 1.3"
4- KAPAK UZUNLUĞU (SLIDE LENGTH)	158 mm / 6.2"
5- KAPAK GENİŞLİĞİ (SLIDE WIDTH)	23.5 mm / 0.9"
6- GÖRÜŞ HATTI (SIGHT RADIUS)	138.5 mm / 5.4"
7- TETİK MESAFESİ (TRIGGER DISTANCE)	68 mm / 2.7"

AĞIRLIKLAR (WEIGHTS)

ŞARJÖRSÜZ TABANCA (WITHOUT MAGAZINE)	550 g / 19.4 oz
BOŞ ŞARJÖRLÜ TABANCA (WITH EMPTY MAGAZINE)	615 g / 21.7 oz
DOLU ŞARJÖRLÜ TABANCA (WITH LOADED MAGAZINE)	765 g / 27 oz

ÜRÜN ÖZELLİKLERİ (PRODUCT FEATURES)

- POLİMER GÖVDE (POLYMER FRAME)
- SOĞUTMA KANALLI KAPAK (SLIDE WITH COOLING CHANNELS)
- OPTİK NİŞANGAH UYUMLU KAPAK KESİMİ (OPTIC READY SLIDE CUT)
- AKSESUAR RAYI (PICATINNY RAIL)
- DİK TETİK KORKULUĞU (VERTICAL TRIGGER GUARD)
- KOLAY KURULUM İÇİN AGRESİF KAPAK ÇİZGİLERİ (AGGRESSIVE COVER STRIPES FOR EASY INSTALLATION)

REV:0 - 24/01/2024

SARSILMAZ SİLAH SANAYİ A.Ş.
Düzce 1. Organize Sanayi Bölgesi
5. Cadde No:12 Beyköy Beldesi
Düzce / TÜRKİYE

TELEFON:
+90 (380) 548 8011
FAKS:
+90 (380) 548 85 63

E-MAIL:
sarsilmaz@sarsilmaz.com



sarsilmaz.com

